



Specjalne trzonki

Oznaczenie	Moc (W)	Napięcie emitera (V)	Napięcie (V)	Zapłonnik	Natężenie (A)	Spec. moc (W/cm)	Długość łuku (mm)	Długość całkowita (mm)	średnica (mm)	Rysunek referencyjny	Konektor	Typ Nr. Spektrum 1	Typ Nr. Spektrum 2	Typ Nr. Spektrum 3
UVH 1022-0	1000	145	230	X	7.5	100	106	230	22.5	1	PTFE-przewód	24015002		
UVH 1224-0	1000	130	230	X	8.6	80	120	215	24.5	2	PTFE-przewód (1)	24025502		
UVH 1322-0	1300	150	230	X	9.7	100	125	230	22.5	1	PTFE-przewód	24028502		
UVH 1522-0	1500	150	230	X	11	100	152	275	22.5	1	PTFE-przewód	24035002		
UVH 1522-1	1500	150	230	X	11	100	152	275	22.5	1	PTFE-przewód (2)	24040502		
UVH 1522/28-0	1700	275	400	X	7	115	152	275	22.5	1	PTFE-przewód	24037002		
Q-3022 S-1	2500	500	750	X	5	80	305	420	22.5	7	PTFE-przewód	24073902		
UVH 2022-0	2000	240	400	X	9.7	100	206	330	22.5	1	PTFE-przewód	24045102	24001102	
UVH 2022-3	2000	240	400	X	9.7	100	206	330	22.5	1	PTFE-przewód	24049902		
UVH 2420-0	2000	210	400	X	9.5	80	250	361	19.5	1	PTFE-przewód (1)	24115402		
UVH 1524-1	2250	150	230	X	16	150	152	275	24.5	1	PTFE-przewód (2)	24306802		
UVH 2026-1	2400	270	400	X	10	120	206	330	26.5	1	PTFE-przewód	24315502		
UVH 2522-0	2500	280	400	X	10	100	247	380	22.5	1	PTFE-przewód	24055002		
UVH 3022-0	3000	275	400	X	12	100	305	430	22.5	1	PTFE-przewód	24065002		
UVH 3023-0	3000	265	400	X	12	120	250	350	22.5	2	Silikon-przewód	24717002	24727002	
Q-2722-0	2700	280	400	X	10.7	100	272	365	19.5	7	PTFE-przewód	24376002		
UVH 3522/28-0	3600	275	400	X	14.5	100	356	480	22.5	1	PTFE-przewód	24074002	24077502	24074102
UVH 3026-3	3700	230	400	X	18	120	300	410	26.5	3	PTFE-przewód (3)	24338002		
UVH 2524-0	4000	280	400	X	16	160	250	329	24.5	3	PTFE-przewód	24059502		
UVH 4024-0	4000	360	570		12	150	256	380	24.5	1	PTFE-przewód	24385102		
UVH 4026-0	4000	360	570		12	150	256	380	26.5	1	PTFE-przewód (1)	24385202		
UVH 4122-0	4100	270	400	X	16	100	425	550	22.5	1	PTFE-przewód	24085002		
UVH 4222-0	4200	600	1000		8	100	425	550	22.5	1	PTFE-przewód	24095002		
UVH 5022/45-0	5000	440	660	X	12.4	100	505	630	22.5	1	PTFE-przewód	24125002		
UVH 5822/45-0	5800	440	660	X	14.5	100	585	710	22.5	1	PTFE-przewód	24115102		
UVH 5822-0	5800	725	1200		9	100	585	710	22.5	1	PTFE-przewód	24105102	24106002	
UVH 6722-0	6700	850	1500		9.3	100	680	800	22.5	1	PTFE-przewód	24135002		
UVH 6426-0	6900	630	950		12	170	406	530	26.5	1	PTFE-przewód (1)	24417002		
UVH 7322-0	7300	900	1500		9	100	740	860	22.5	1	PTFE-przewód	24145002		
UVH 8322-0	8300	1000	1700		9.3	100	829	939	22.5	1	PTFE-przewód (1)	24155002		
UVH 10022-0	10000	1250	2200		9	100	1005	1130	22.5	1	PTFE-przewód	24175002		
UVH 11022-0	11000	1500	2300		8.6	100	1105	1230	22.5	1	PTFE-przewód	24195002		
UVH 14021-0	11000	1870	2500		6.5	80	1397	1575	19.5	6	Metal	24244002	24407002	
UVH 14219-2	11000	1870	2800		6.3	80	1420	1575	19.5	6	PTFE-przewód	24207502	24206502	
UVH 10522-0	11700	1530	2300		8.5	110	1055	1180	22.5	1	PTFE-przewód	24185002		
UVH 12522-0	12500	1600	2600		9.2	100	1265	1390	22.5	1	PTFE-przewód (2)	24215002		
UVH 13022-0	13000	1970	3000		7.6	100	1305	1430	22.5	1	PTFE-przewód	24225002	24226002	
UVH 14022 G-0	14000	1950	3000		8	100	1405	1530	22.5	1	PTFE-przewód	24201502		
UVH 14219-0	14200	1900	2500		8.3	100	1420	1575	19.5	6	Metal	24209502	24204502	
UVH 14222-1	14200	1900	2500		8.3	100	1420	1575	22.5	1	PTFE-przewód	24236502	24237502	
UVH 14522-0	14500	1900	3000		9	100	1455	1580	22.5	1	PTFE-przewód	24245002		
UVH 16522-0	16500	2000	3200		9.2	100	1655	1780	22.5	1	PTFE-przewód	24265002	24269002	
UVH 10526-0	16800	1850	3200		9.6	160	1055	1180	26.5	1	PTFE-przewód	24485002		
UVH 14222-0	16800	1850	2500		9.9	120	1420	1548	22.5	1	PTFE-przewód	24235002	24236002	
UVH 19022-0	19000	2400	4000		8.8	100	1905	2030	22.5	1	PTFE-przewód	24275002		
UVH 20022-0	20000	2500	4000		9	100	2005	2130	22.5	1	PTFE-przewód	24285002		
UVH 14526-0	23200	2000	3200		12.3	160	1455	1580	26.5	1	PTFE-przewód	24248002		
UVH 22024-0	26400	2500	4000		11.2	120	2205	2330	24.5	1	PTFE-przewód	24296002		



Standardowe trzonki

